1	What is claimed is:
2	
3	1. An apparatus for controlling a hot water washing of a washing machine,
4	comprising:
5	a water supply unit supplying water according to an inputted control signal;
6	a heater unit heating the water up to a predetermined temperature according to the
7	inputted control signal;
8	a sensor unit sensing whether a water level of the water is a heating water level for
9	heating or a washing water level for washing, the sensor unit sensing a temperature of the
10	water; and
11	a control unit controlling the water supply unit and the heater unit according to a
12	sensing signal of the sensor unit.
13	
14	2. The apparatus as claimed in claim 1, wherein the heating water level is a
15	water level under which the heater unit is completely submerged.
16	
17	3. The apparatus as claimed in claim 2, wherein the heating water level is
18	20~30% of the washing water level.
19	
20	4. The apparatus as claimed in claim 1, wherein the washing machine is a drun
21	type washing machine.
22	
23	5. In a washing machine including a water supply unit supplying water, a heate
24	unit heating the water, a sensor unit sensing a water level of the water, and a control uni

a:

25	controlling the water supply unit and the heater unit, a method of controlling a hot water
26	washing of the washing machine, comprising the steps of:
27	setting a washing condition for the hot water washing;
28	supplying the water according to the set washing condition;
29	judging whether the water level of the supplied water is a heating water level for
30	heating the water;
31	heating the water if the water level of the water is the heating water level;
32	judging whether the water level of the supplied water is a washing water level
33	according to the set washing condition;
34	if the water level of the supplied water is the washing water level according to the set
35	washing condition, judging whether a temperature of the water is a heating temperature
36	according to the set washing condition; and
37	if the temperature of the water is a heating temperature according to the set washing
38	condition, executing the hot water washing.
39	
40	6. The method as claimed in claim 5, wherein the washing machine is a drum
41	type washing machine.
42	
43	7. The method as claimed in claim 5, wherein the washing condition for the hot
44	water washing includes the water level and the temperature of the water.
45	
46	8. The method as claimed in claim 5, further comprising the step of driving the
47	water supply unit prior to the step of supplying the water.

- The method as claimed in claim 5, wherein, in the step of judging whether 9. 49 the water level of the supplied water is the heating water level for heating the water, the step 50 of supplying the water is repeated if the water level of the water is not the heating water level. 51 52 The method as claimed in claim 5, further comprising the step of driving the 10. 53 heater unit prior to the step of heating the water. 54 55 The method as claimed in claim 5, wherein, in the step of judging whether 11. 56 the water level of the supplied water is the heating water level for heating the water, the 57 heating water level is a water level under which the heater unit is completely submerged. 58 59 The method as claimed in claim 11, wherein the heating water level is 12. 60 20~30% of the washing water level. 61 62 The method as claimed in claim 5, in the step of judging whether the water 13. 63 level of the supplied water is the washing water level according to the set washing condition, 64 the current step is repeated if the water level of the supplied water is not the washing water 65 level according to the set washing condition. 66 67 The method as claimed in claim 5, further comprising the step of stopping 14. 68 driving the water supply unit prior to the step of judging whether the temperature of the water 69
- The method as claimed in claim 5, wherein in the step of judging whether the

is the heating temperature according to the set washing condition.

70

71

- temperature of the water is the heating temperature according to the set washing condition,
- the current step is repeated if the temperature of the water is not the heating temperature
- according to the set washing condition.

76

77 16. The method as claimed in claim 5, further comprising the step of stopping
78 driving the heater unit prior to the step of executing the hot water washing.